



SatLight

Satlight is an additional light that can be powered from the main GravityLight unit (GL02). Multiple Satlights can be linked together (reccomended max. of 4).

SatLight weight	41 g / 1.45 oz
Nominal Voltage*	2.7 V DC
Max current*	0.031 A
Max electrical power*	0.085 W
Luminous flux	15 lm
Luminous efficiency	208 lm/W
Colour temperature	5000 K
Colour Rendering Index	> 70
Beam angle	84°
IP rating	IP2X

SatLight power cable

Cable length	5 meters
Connector type	3.5mm stereo jack

Complies with:



CE
General Product Safety
Directive 2001/95/EC
EMC Directive 2014/30/EU
IEC/EN/BS 55015
IEC/EN/BS 61547
IEC/EN/BS 61000-3-2
IEC/EN/BS 61000-3-3
IEC/EN/BS 62493
IEC/EN/BS 62471
RoHS Directive 2011/65/EU
WEEE Directive 2012/19/EU
IEC/EN/BS 60598-1
IEC/EN/BS 60598-2-4
FCC Part 15

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation

*Electrical output based on max loaded bag weight

NOTE: Deciwatt reserve the right to alter data, specifications and component parts without prior notice.